

PRODUCT DATA

HOCUT B 205-O

HOCUT B 205-O is a water-soluble, stabilizing, corrosion concentrate for use in Phase Control systems in conjunction with the vegetable-based soluble oil HOCUT TR 2000-C.

INTENDED USE

The functional of **HOCUT B 205-O** is to provide bio-resistance, corrosion inhibition and maintain the overall Phase Control coolants' pH.

APPLICATION

To be used in conjunction with HOCUT TR 2000-C at the typical range of 1.5 to 1.8%, dependent on water quality.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Appearance, neat	Clear Yellow fluid
Appearance, 1% dilution	Transparent
pH, 1% dilution	9.5
Method of Control:	Refractive index or Alkalinity Titration
Foaming Tendency with Hocut TR 2000-C	max. of 6mm foam cuff after 10 sec



HOUGHTON CANADA INC.

P.O. Box 113, Station "D"
100 Symes Rd.
Toronto, Ontario M6P 3J5
Ph (416) 763-4691 • Fx (416) 763-3167
www.houghton.ca



AVAILABILITY

HOCUT B 205-O is available in bulk, 1100-litre capacity tote bins, 205 litre drums and 20 litre pails.

SHELF LIFE

One (1) year

STORAGE/HANDLING/DISPOSABILITY

No health or safety hazards exist when **HOCUT B 205-O** is stored, used and disposed of in accordance with instructions given on the Material Safety Data Sheet for this product.

WARRANTY

The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied since the use of our products is beyond our control. Statements concerning the use of Houghton products are not to be construed as recommending the infringement of any patent.

April 2, 2003