

---

# Superdraw ST20

---

## *Cold Drawing Lubricant*

### DESCRIPTION

Superdraw ST20 is a highly enhanced lubricant containing high levels of lubricity additives and chlorinated EP additives; it is suitable for the most extreme operations.

### APPLICATION

Superdraw ST20 gives excellent performance when used for cold reducing stainless steel tubes and deep drawing stainless and high nickel alloys assisting metallic flow through considerable reductions in both diameter and wall thickness. This product is also suitable for use as a conventional blanking and stamping and fine blanking lubricant where it performs the most arduous tasks.

### FEATURES

Excellent boundary lubrication

High performance EP additive system

Suitable for various materials

Suitable for various applications

Low odour

### BENEFITS

Good surface finish and prevents tearing on thin walled components

Improved tool and die life

Versatile

Versatile

Operator acceptable

### TYPICAL PHYSICAL CHARACTERISTICS

Appearance	clear amber liquid
Relative density @ 20°C	1.10
Kinematic viscosity @ 40°C	20cSt
Closed flash point	> 170°C
Pour Point	-9°C

### METHOD OF USE

Superdraw ST40 can be applied using re-circulatory systems, roller coaters or by manual application.

It can be removed with the following specialist cleaners:

Solvent 601 – low hazard modified alcohol cleaner.

Solvent 702 – non-VOC solvent cleaner.