

## Polartech DA 8001

Complex Organic Synthetic Corrosion Inhibitor

- Use** : Corrosion inhibitor
- Applications** : Semi synthetic watermix cutting fluid  
Synthetic watermix cutting fluid  
Industrial cleaning fluids
- Advantages** : Excellent corrosion inhibition on ferrous and non ferrous  
Potentially non staining on aluminium and its alloys  
Readily soluble in water, glycols and polyglycols  
Compatible with hard water  
Secondary amine free  
Super low foaming tendency
- Concept** : A multi metal corrosion inhibitor, readily soluble in aqueous systems.

### Typical Product Data

<b>Appearance</b>	:	Pale yellow, clear fluid
<b>Chemical Type</b>	:	Alkanolamine soap of mono and di-carboxylic acids
<b>Specific Gravity @ 20°C</b>	:	1.17
<b>Boron Content %wt</b>	:	1.0
<b>pH @ 1% Concentration</b>	:	7.7
<b>Total Alkalinity % wt KOH</b>	:	16
<b>IP 287 Corrosion Test %</b>	:	1.0

This does not represent a complete specification, full sales specification data will be supplied on request by Polartech Quality Assurance Department.

### Health and Safety

Polartech DA 8001 is free from secondary amines, nitrites, phenols, chlorine and PTBBA in accordance with international health and safety trends. For a full Material Safety Data Sheet please contact Polartech Limited.

Polartech DA 8001 forms part of a comprehensive range of additives, if you require more information on this or any other product please contact Polartech Technical Department. This information is for guidance only. It is recommended that complete testing be carried out on all additives to determine their suitability for use in proprietary formulations.



### POLARTECH LIMITED

ASHBURTON ROAD WEST, TRAFFORD PARK, MANCHESTER M17 1SX, ENGLAND  
TELEPHONE: 44 (0) 161 876 5673 FAX: 44 (0) 161 872 1922 email: [company@polartech.co.uk](mailto:company@polartech.co.uk)