



TECHNICAL DATA

ULTRACUT 290A

High Performance Low Foaming Long Life
Cutting Fluid for Aluminium

TECHNICAL DATA

Description

ROCOL ULTRACUT 290A is a high performance, low foaming, water mix, aluminium cutting fluid uniquely formulated for high pressure, high throughput, CNC systems. It provides extra performance in medium and severe cutting operations when machining aluminium and its alloys whilst promoting optimum surface finish. ROCOL ULTRACUT 290A can also be used to machine non ferrous metals, for example, copper and its alloys and all but the most difficult to machine ferrous metals.

Outstanding Features

- Optimised emulsification package designed for high pressure, high throughput CNC systems
- Low foaming
- Provides optimum cutting performance on aluminium and its alloys
- Prevents built-up edge
- Promotes excellent surface finish
- Non-staining with most aerospace and industrial alloys
- Excellent residual corrosion protection
- Inherently resistant to degradation
- Long and predictable sump life
- Rejects tramp oil
- Pleasant and safe to use

Directions for use

Recommended dilution: ROCOL Ultracut 290A should be used between 15:1 and 25:1 depending on the severity of the operation, workpiece material and water hardness. To ensure dilution accuracy, it is preferable to use a ROCOL Automatic Fluid Mixer. For manual mixing, add the concentrate to water at the recommended dilution ratio, stirring continuously.

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers.

There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility

It is advisable to use the appropriate ROCOL Ultraguard Machine Tool Care product at fluid changeovers. Optimum fluid life is obtained by adequate initial machine cleaning, correct dilution control and regular maintenance of fluid, particularly prior to weekends and shutdown periods.

Technical Data (typical values)

Appearance: Clear amber liquid forming a white emulsion when mixed with water

Odour: Mild

pH: 8.7 at 20:1

Density at 20°C: 0.95 g/cm³

Storage: Store at normal ambient temperature (5 to 30°C)

Refractometer calibration:

Dilution ratio	10:1	15:1	20:1	25:1	30:1
Refractometer reading	9.4	6.3	5.5	4.1	3.3

Pack sizes and part codes

1000 ltr part code 51835

Health and Safety

Safety data sheet is available from the Customer Service Department, ROCOL Lubricants. ROCOL House, Swillington, Leeds, LS26 8BS, England.

Telephone: 0113 232 2700, (When calling from outside UK: 44 113 232 2700).

Fax: 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: Ultracut 290A TDS 5183

Date: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers.

There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility