



TECHNICAL DATA

ULTRACUT 560

Chlorine Free Extreme Pressure
Neat Oil Cutting Fluid

TECHNICAL DATA

Description

ROCOL ULTRACUT 560 is a pale coloured extreme pressure neat cutting oil formulated from severely refined mineral oil, lubricity additives and non-chlorinated EP performance additives. ROCOL ULTRACUT 560 provides excellent cutting performance and improves tool life.

ROCOL ULTRACUT 560 is suitable for a wide range of applications on automatic and multi-tool lathes even when machining high tensile steels. It is also suitable for specialised operations such as production thread grinding, broaching, hobbing and multi-cutter milling set-ups. It is not suitable for use on copper or copper based alloys.

Outstanding Features

- Pale coloured
- Low odour
- Excellent extreme pressure properties
- Improves tool life
- Good heat transfer properties

Directions for use

ROCOL ULTRACUT 560 is supplied ready for use. Guard against water ingress.

Technical Data (typical values)

<i>Appearance:</i>	<i>Pale yellow liquid</i>
<i>Odour:</i>	<i>Mild</i>
<i>Viscosity at 40°C:</i>	<i>32 cSt</i>
<i>Density at 20°C:</i>	<i>0.88 g/cm³</i>
<i>Storage:</i>	<i>Store at normal ambient temperature (5 to 30°C)</i>

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility

ULTRACUT 560

Pack sizes and part codes

200 ltr part code 51629

Health and Safety

Safety data sheet is available from the Customer Service Department, ROCOL Lubricants, ROCOL House, Swillington, Leeds, LS26 8BS, England.

Telephone: 0113 232 2700, (When calling from outside UK: 44 113 232 2700).

Fax: 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: Ultracut 560 TDS 5162

Date: Jan-03

TECHNICAL DATA

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers.

There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility