



TECHNICAL DATA
ULTRACUT 620
Extreme Pressure Long Life
Chlorine Free Semi-Synthetic Cutting Fluid

TECHNICAL DATA

Description

ROCOL Ultracut 620 is an extreme pressure, chlorine free, semi-synthetic water mix cutting fluid formulated to give a long and predictable sump life. It provides extra performance in medium/severe cutting operations on a wide range of ferrous and non-ferrous metals. The combination of extreme pressure performance, excellent corrosion and staining inhibition and long sump life permits increased production rates and provides cost effective use.

ROCOL Ultragrind 620 can also be used as a grinding fluid enabling the user to rationalise to one fluid for both cutting and grinding operations.

Outstanding Features

- Contains no chlorinated additives
- Extends tool life
- Promotes excellent surface finish
- Suitable for cutting and grinding operations
- Suitable for medium/severe cutting operations
- Long and predictable sump life
- Inherently resistant to degradation
- Suitable for use with a wide range of ferrous and non-ferrous metals
- Inhibits corrosion and staining
- Resists foaming
- Emulsifies tramp oil
- Translucent emulsion gives good view of work piece

Directions for use

Recommended dilution: ROCOL Ultracut 620 should be used between 20:1 and 40:1 for cutting and 40:1 to 55:1 for grinding depending on the severity of the operation, workpiece material and water hardness. To ensure dilution accuracy, it is preferable to use a ROCOL Automatic Fluid Mixer.

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility

For manual mixing, add the concentrate to water at the recommended dilution ratio, stirring continuously.

It is advisable to use the appropriate ROCOL Ultraguard Machine Tool Care product at fluid changeovers. Optimum fluid life is obtained by adequate initial machine cleaning, correct dilution control and regular maintenance of fluid, particularly prior to weekends and shutdown periods.

Technical Data (typical values)

<i>Appearance:</i>	<i>Blue concentrate forming a semi-translucent blue emulsion</i>
<i>Odour:</i>	<i>Mild</i>
<i>pH:</i>	<i>9.5 at 15:1</i>
<i>Density at 20°C:</i>	<i>1.00 g/cm³</i>
<i>Storage:</i>	<i>Store at normal ambient temperature (5°C to 30°C)</i>

Refractometer calibration:

Dilution ratio	10:1	20:1	30:1	40:1	50:1	60:1
Refractometer reading	8.7	5.0	3.1	2.3	1.9	1.7

Pack sizes and part codes

20 ltr	part code 51383
200 ltr	part code 51389

Health and Safety

Safety data sheet is available from the Customer Service Department, ROCOL Lubricants., ROCOL House, Swillington, Leeds, LS26 8BS, England.

Telephone: 0113 232 2700, (When calling from outside UK: 44 113 232 2700).

Fax: 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: Ultracut 620 TDS 5138
Date: Jan-04

ROCOL Lubricants

ROCOL House, Swillington, Leeds LS26 8BS, England.

Tel: 0113 232 2600 Fax: 0113 232 2760

ROCOL is a BS EN ISO 9001 registered company.

ROCOL is a trade mark of ITW inc

The information in this publication is based on our experience and reports from customers.

There are many factors outside our control and knowledge which effect the use and performance of our products for which reason the information in this publication is given without responsibility